ADVANCE TABCO
SMART FABRICATION™

STAINLESS STEEL
FABRICATED
SUPERSIZE SINKS

NEW *Tile Edge Design*

Model # K7-3-2030-24RL Shown

NSF

Item #: _____ Qty #: _____	
Model #: _____	
Project #: _____	

FEATURES:

Tile edge for ease of installation.

16 gauge, 304 series stainless steel.

14" Deep Bowls.

Fabricated design.

Extra Large Sink bowls fabricated to meet NSF specifications with a 3/4" radius.

Placement of the welded leg assembly insures stability and furnishes direct support of the column load requirements for the entire sink unit.

Cross bracing on side legs.

Full skirt design.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Gussets welded to a die-embossed reinforcing channel.

MECHANICAL:

Faucet holes provided.

Faucet holes on 8" centers.

Faucets are not included (see accessories).

Waste drains are 1 1/2" IPS basket type and are included.

14" Water Level.

MATERIAL:

Entire unit is 16 gauge type "304" series stainless steel.

LEGS are 1 5/8" diameter heavy gauge tubular stainless steel with stainless steel gussets and 1" adjustable stainless steel bullet feet.

MODEL #	Bowl Size (B) x (A) x 14"	# of Comp.	Drbd. Size (D)	Overall Size (L) x (W)	(X)	Weight	Cu. Ft.
K7-3-1432-18RL*	14" x 32" x 14"	3	18"	78" x 38"	19"	290 lbs.	50
K7-3-2030-24RL*	20" x 30" x 14"	3	24"	108" x 36"	18"	345 lbs.	78
K7-3-2430-24RL	24" x 30" x 14"	3	24"	120" x 36"	18"	380 lbs.	86
K7-3-3024-24RL	30" x 24" x 14"	3	24"	138" x 30"	15"	395 lbs.	84
K7-3-3030-24RL	30" x 30" x 14"	3	24"	138" x 36"	18"	420 lbs.	98

REQUIRED ACCESSORIES	Model #
DRAINS	
FAUCETS	

* Provided with 1 set of faucet holes

*** For <u>14 Gauge Units</u> Add -14 at end of Model Number ***

ADVANCE TABCO
SMART FABRICATION™
www.advancetabco.com

Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:
Email: customer@advancetabco.com or **Fax:** 631-242-6900

For Smart Fabrication™ Quotes:
Email: smartfab@advancetabco.com or **Fax:** 631-586-2933

E-12

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500"
Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL

K7-3-2430-24RL, K7-3-3024-24RL, K7-3-3030-24RL

Two Faucet Configuration

K7-3-2030-24RL & K7-3-1432-18RL

Single Faucet Configuration