

Shown

STAINLESS STEEL

Drop-In Ice Bins



Item #:	Qty #:
Model #:	
Project #:	

FEATURES:

11" deep ice bin.

Optional 7-Circuit cold plate sealed into the bottom. Rubber thermal breaker reduces condensation. Includes stainless steel sliding cover.

MECHANICAL:

1" IPS drain (non-cold plate models) 1/2" IPS drain (cold plate models)

MATERIAL:

Ice Bin: 20 gauge, 300 stainless steel Jacket: 20 gauge galvanized steel Cover: 20 gauge stainless steel

Ice Bin Insulation: 2 lbs. density foam-in-place

Molding: Extruded black polyethylene thermal breaker marine edge

Model #	Dimension (L)	Dimension (B)	Cut Out Size W x L	Ice Capacity	Approx. Weight	Approx. Cu. Ft.
D-12-IBL	12"	6"	15 1/4" x 9 5/8"	23 lbs.	22 lbs.	3
D-24-IBL	21"	10 1/2"	15 1/4" x 20 3/8"	50 lbs.	39 lbs.	5
D-30-IBL	27"	13 1/2"	15 1/4" x 26 3/8"	62 lbs.	62 lbs.	8
D-36-IBL	33"	16 1/2"	15 1/4" x 32 3/8"	75 lbs.	67 lbs.	9

With 7-Circuit Cold Plate

D-24-IBL-7	21"	10 1/2"	15 1/4" x 20 3/8"	50 lbs.	84 lbs.	5
D-30-IBL-7	27"	13 1/2"	15 1/4" x 26 3/8"	62 lbs.	107 lbs.	8
D-36-IBL-7	33"	16 1/2"	15 1/4" x 32 3/8"	75 lbs.	113 lbs.	9

Model #	For Use With:	
D-12	D-12-IBL, D-24-WSIBL, D-24-WSIBL2, D-24-SIBL	
D-24	D-24-IBL, D-24-IBL-7	
D-24V	D-24-IBL, D-24-IBL-7 Units oriented with 18" dimension left-to-right	D-12 Show
D-30	D-30-IBL, D-30-IBL-7	
D-36	D-36-IBL. D-36-IBL-7	-



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:


Email: smartfab@advancetabco.com or Fax: 631-586-2933


DIMENSIONS and SPECIFICATIONS


TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL

Non-Cold Plate Models







Cold Plate Models

