



DROP-IN SINKS One Compartment - FOR GENERAL PURPOSE USE









LARGEST ONE **COMPARTMENT DROP-IN SINK IN** THE INDUSTRY! Supplied with K-53 Faucet DI-1-2812 16 Gauge

FEATURES:

18 Gauge

One piece seamless Deep Drawn sink bowl design.

All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.

Self-Rim Design. Mounting clips provided accommodates all thicknesses of counter. (Quantity supplied varies based on drop in sink ordered).

DI-1-30 & DI-1-168: includes 4" O.C. K-52 faucet. DI-1-208 & DI-1-2012: includes 4" O.C. K-50 faucet. **DI-1-2812:** includes 4" O.C. **K-53** faucet.

CONSTRUCTION:

Unit fabricated from one sheet of stainless steel. All bowls are Sound Deadened. Units feature Advance Tabco's **Smart Finish**TM.

MECHANICAL:

Faucet supply is 1/2" IPS male thread. Deck mounted faucet is furnished with aerator.

MATERIAL:

Type 304 series stainless steel. Faucets are brass-nickel plated. Stainless Steel 1-1/2" IPS basket drain.

| Available Faucets & Accessories | Model # | Qty |
|--|---------|-----|
| Deck Mounted 8" Swing Spout. 4" O.C. | K-50 | |
| Deck Mounted Gooseneck. 4" O.C. | K-52 | |
| Deck Mounted. 12" Swing Spout. 4" O.C. | K-53 | |
| Deck Mounted 8 1/2" Gooseneck. 4" O.C. | K-55 | |
| Deck Mounted Swing w/Spray. 8" O.C.* | K-58 | |
| Deck Mtd. X.H.D. 3 1/2" Gooseneck. 4" O.C. | K-62 | |
| Mounting Clips (Bag of 4). | K-28 | |

*REQUIRES K-472 FAUCET HOLE REVISION



STANDARD MOUNTING CLIPS

For countertops over 7/8" and up to 2" thick. Replacement # K-28 (Per Sink)



Conforms To NSF 61/9 Lead Free Requirements

CA Prop 65 WARNING: This product may contain a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL ± .125" ALL DIMENSIONS ARE TYPICAL



