

STAINLESS STEEL

HAND SINKS PANEL VALVE





Conforms To NSF 61/9 Lead Free Requirements

Item #:	Qty #:
Model #:	
Project #:	



7-PS-44

Keyhole Bracket for easier installation and greater stability.



FEATURES:

One piece Deep Drawn sink bowl design.

Sink bowl is 10" x 14" x 5" deep.

Stainless steel Apron bolts to sink. Apron conceals plumbing on all three sides.

Faucet activated by push of front panel.

Hot water adjustment valve accessed by raising front of panel.

All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.

"Hands Free" splash mounted gooseneck faucet furnished with aera-

Keyhole wall mount bracket.

Stainless steel basket drain 1-1/2" IPS.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish. Die formed Countertop Edge with a 3/8" No-Drip offset.

One sheet of stainless steel - No Seams.

MATERIAL:

Heavy gauge type 304 series stainless steel.

Wall mounting bracket is galvanized steel and of offset design.

All fittings are brass / chrome plated unless otherwise indicated.

MECHANICAL:

Spout supply is 1/2" IPS male thread.

Valve is barrel type and is activated by pushing the front of panel. (Contractor on site must connect faucet to knee operated valves.)

WARNING:

Equipment that includes a faucet may expose you to chemicals, including lead, that are known to the State of California to cause cancer or birth defects or other reproductive harm. For more Info., visit www.p65warnings.ca.gov.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

REF-B

DIMENSIONS and SPECIFICATIONS

FITTINGS SUPPLIED AS SHOWN TOL Overall: ± .500" Interior: ± .250"



