Item #:	Qty #:
Model #:	
Project #:	



Brackets Easily Snaps In On Both Ends

Brackets Are In A Fixed Position

ALL DIMENSIONS ARE TYPICAL

FEATURES:

Furnished with a 1-5/8" Bullnose edge with a 1-1/4" turn-up edge on sides and rear.

Unit is easily assembled employing the slip-fit TAB-LOK design.

CONSTRUCTION:

Shelf and brackets are die stamped and die formed.

MATERIAL:

TOL ± .500"

WS-KD Series - 18 gauge stainless steel polished to a satin finish. AWS-KD Series - Heavy gauge aluminum.

SHELF WITH SNAP-IN END BRACKETS

S/S	ALUMINUM	Width	Length	Wt.	Cu.
WS-KD-24	AWS-KD-24	11 1/8"	24"	10 lbs.	1
WS-KD-36	AWS-KD-36	11 1/8"	36"	12 lbs.	1
WS-KD-48	AWS-KD-48	11 1/8"	48"	14 lbs.	1
WS-KD-60	AWS-KD-60	11 1/8"	60"	17 lbs.	1

DETAILS and SPECIFICATIONS

1-1/4" Length 11 1/8" 9 1/2" Requirements for NSF Installations 1. Install at least 60" above floor. 2. Limit to dry storage. 3. Avoid contact with liquids. 4. For "Ganging-Up" installation, allow at least 2" between units or mount units side by side and seal joints with an approved sealant.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933