

**FEATURES:** 

8 1/2" high backsplash. 8" sink bowl depth.

clearance underneath.

Single holes provided.

All TIG welded.

to a satin finish.

**CONSTRUCTION:** 

Two stainless steel "Z" brackets.

One K-6 3 1/2" rear basket drain.

Die formed tubular wall brackets

Two tubular stainless steel support brackets that allow full

Welded areas blended to match adjacent surfaces and

Electronic Operated: Includes four K-175 Electronic Faucets.

## **16 GAUGE STAINLESS STEEL** FOUR STATION WALL MOUNTED SQUARE CORNER SERVICE SINK WITH TUBULAR SUPPORTS **ELECTRONIC OPERATED**



ltem #:	Qty #:	
Model #:		
Project #:		_





#### Hands-Free Electronic Faucet


#### **MATERIAL:**

All 16 gauge type "304" stainless steel. 1 5/8" tubular "304" stainless steel wall brackets.

Stainless steel gussets.

### **MECHANICAL:**

Single faucet holes.



#### MULTI-STATION ACCESSORIES & REPLACEMENT PARTS FLOOR STANDING LEGS MODIFICATION K-13 K-175 K-411 Converts Wall Mounted 19-18 SERIES Sink To A Free Standing Floor Unit. Model Description QTY: Stainless Steel Legs with Flanged Feet · Sides and Rear Cross Bracing **K-6** 3 1/2" Drain (1 1/2" I.P.S.) Fits Sink Stainless Steel Soap Dispenser (Wall Mount Only) Model # QTY: 📁 K-13 Length FS-CB-80 📁 K-175 Single Hole, Splash Mounted 3-1/2" Electronic Faucet 80' Strainer Plate for 3-1/2" Drain 🎁 K-411 K-508 Special Sizing Charge (Larger Size Cut Down To Smaller Size) Adjustable Stainless Steel Flanged Bullet Foot 🕋 TA-19 📁 = Ships UPS Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards. 🛕 WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.



For Orders & Customer Service:

For Smart Fabrication<sup>™</sup> Quotes:

Email: customer@advancetabco.com or Fax: 631-242-6900

Email: smartfab@advancetabco.com or Fax: 631-586-2933

# **DETAILS and SPECIFICATIONS**

TOL ± .500"

