

# Gas Ranges with Griddle Tops

## Standard Features

- Stainless steel exterior including front, back sides, kick plate, back guard and over shelf
- Heavy duty 3/4” thick polished steel griddle plate
- Drip tray provided under burners to catch grease drippings
- 27,000 BTU griddles & 27,000 BTU oven burners
- Oven temperature range between 175°F to 550°F
- Standing pilot for open top burners
- Oven pilot with 100% safety shut off
- Enamel interior oven for easy cleaning
- Multiple position oven rack guides
- Two(2) chrome oven racks per oven standard
- Available in Natural and Propane
- 3/4” NPT rear gas connection and regulator provided
- Four(4) casters standard

## Optional Accessories

- Leg kit part #: 301110006
- AGR-24G extra oven rack part #: 301100013
- AGR-36G extra oven rack part #: 301100012

### MODELS:

AGR-24G/AGR-36G



**AGR-24G**



**AGR-36G**



1 YEAR PARTS AND LABOR WARRANTY



Conforms to ANSI  
STD Z83.11-2009 (2011)  
Certified for CSA  
STD 1.8B-2009 (2011)  
Conforms to NSF/ANSI STD.4



REV. 05/23

**“WE MAKE THE KITCHEN BETTER!”**

**SPECIFICATIONS**

Models	Gas Type	Burner Name	BTU's	Number of Burners	Valve Types	Oven Size (inch)	Griddle Working Area (inch)	Exterior Dimensions (inch)	Net Weight (lbs)	Gross Weight (lbs)
AGR-24G	NG	Griddle	48,000	2	Pilot light	20×26×14	24×20 <sup>5/8</sup>	24×31×57 <sup>3/8</sup>	367	469
		Oven	24,000	1						
	LP	Griddle	48,000	2						
		Oven	24,000	1						
AGR-36G	NG	Griddle	75,000	3	Pilot light	26 <sup>1/2</sup> ×26×14	36×20 <sup>5/8</sup>	36×31×57 <sup>3/8</sup>	494	622
		Oven	27,000	1						
	LP	Griddle	75,000	3						
		Oven	27,000	1						

**PLAN VIEW**



Dripping hole



Stainless steel drawer



Stainless steel knobs



Logo

