


Project:	AIA#
Item:	
Location:	SIS#
Approved:	

# WTR 29" DEPTH WORKTOP

WTR60AHC Worktop Refrigerator with Flat Top Hydrocarbon Series

**MODELS:** WTR60AHC-FLT





#### **CABINET CONSTRUCTION**

- Stainless steel front, sides and doors, (galvanized back & bottom)
- Interior liner is made of corrosion resistant aluminum
- Full electronic control
- Stainless steel worktop
- Flat worktop
- Interior thermometer is standard
- Self-closing doors with 120° stay-open feature, on cartridge style
- Magnetic gasket attached to each door for positive seal
- Painted aluminum door handles
- 6" Casters, two (2) with brakes standard
- Two epoxy-coated steel wire shelves per section standard
- Field-reversible doors
- Maintains product temperature between 36°F and 38°F

#### **REFRIGERATION SYSTEM**

- Refrigeration system uses R290 refrigerant to comply with all environmental concerns
- Automatic, non-electric defrost
- Epoxy coated evaporator coil

# **OPTIONS & ACCESSORIES**

- Stainless steel back and grille
- Stainless steel interior
- Right or left hinged door
- Locks (solid doors only)
- Bun rack
- Wire shelf divider
- Cutting board
- Thermometer digital or stem type dial
- 3" Casters or 6" legs
- Low profile casters
- Remote option


















MODEL	WTR60AHC-FLT
EXTERNAL DIMENSIONAL DATA	
Width Overall	60"
Depth Overall	32"
Height Overall with 6" Casters	35 5/8"
Number of Doors	2
Depth with Door Open 90 °	55 1/4"
Door Opening (in)	22 5/8" x 21 5/8"
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.)	14.75
Internal Width Overall (inches)	56"
Internal Depth Overall (in)	23 1/2"
Internal Depth Useable (in)	Upper 18 1/2" Lower 15 3/8"
Internal Height Front (in)	23"
Internal Height Rear (in)	16"
Number of Shelves	4
ELECTRICAL DATA	
Full Load Amperes 115/60/1	3.0
REFRIGERATION DATA	
Horsepower	1/5
Capacity (BTU/Hr)*	1350
WEIGHT DATA	
Gross Weight (Crated lbs)	300 lbs
Height - Crated	35"
Width - Crated	62"
Depth - Crated	33"

# **Worktop Refrigerator**

Models: WTR60AHC-FLT



### **ELECTRICAL CONNECTION**



115/60/1 NEMA-5-15P Units pre-wired at factory and include 8' long cord and plug set.













