

# EQ-TL-1 Cartridge

10.0" x 4.0" x 4.0"  
(25.4cm x 10.2cm x 10.2cm)

\*Feature points are currently unavailable.\*



Agency:



## Specifications

**Product #:** 30331.1001

**Cartridge Type:** Quick Change

## Additional Features

## Capacity

| Service Flow Rate       | Capacity                                    | Micron Rating |
|-------------------------|---|---------------|
| 1.5 gal/min (5.7 L/min) | 4800 gal. (18169.7 L)<br>@0 GPG of hardness | -             |

## Plumbing Requirements

| Max Operating Pressure | Max Operating Temperature | Inlet Connection | Outlet Connection |
|------------------------|---------------------------|------------------|-------------------|
| 125 psi (862 kPa)      | 100°F(38°C)               | -                | -                 |



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit [bunn.com](http://bunn.com).

Created on:  
09/14/2017

| Unit    |         |          |         | Shipping |        |       |           |        |
|---------|---------|----------|---------|----------|--------|-------|-----------|--------|
|         | Width   | Height   | Depth   | Width    | Height | Depth | Weight    | Volume |
| English | 4.0 in. | 10.0 in. | 4.0 in. | -        | -      | -     | 2.100 lbs | -      |
| Metric  | 10.2 cm | 25.4 cm  | 10.2 cm | -        | -      | -     | 0.953 kgs | -      |



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit [bunn.com](http://bunn.com).

Created on:  
09/14/2017