BASE UNDERCOUNTER FREEZER (0°F)

Model: CFA43-U-D

43" Base Undercounter Freezer with Drawers

Heavy gauge #300 Series stainless steel top, stainless steel front and end panels, galvanized steel rear and grill and aluminum interior.

Designed to maintain NSF-7 temperatures in 100°F ambient.



Options and Accessories

(upcharge and lead times may apply)				
Stainless steel interior	Condensing unit left or right			
Stainless steel back	Automatic, electric condensate evaporator			
Door in lieu of drawers	Door/drawer locks			
Drawer in lieu of half door above the condensing unit	Special electrical requirements (consult factory)			

*Drawer section above condensing unit holds (1) 12 x 20 x 6 pan

Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance-rated refrigeration system

Environmentally-safe R-404A refrigerant

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, energy saving, non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide-out condensing unit

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Spring loaded, self closing door (over condensing unit)

Magnetic snap-in door/drawer gaskets

Stainless steel roll-out drawers

Completely enclosed, vented and removable rear and side grills

Refrigerated section with door above the condensing unit

(8) 1 3/8" diameter plate casters mounted on heavy-duty support plates (easily field installed)

MODEL FEATURES

Electronic controller w/ digital display & hi-low alarm

Front breather air divider (field installed)

Expansion valve for quick recovery

Automatic electric defrost

NOTE: CFA-U models come standard with a door over the condensing unit. A drawer over the condensing unit is an option.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Model Specifications

Model Plan Views

n	ME	N SI		A I	пл	TE /
UI			UN	AL.	DR	

DIMENSIONAL DATA			
Net Capacity (cu. ft.)	12 (340 cu l)		
Width, Overall (in.)	43 (1092 mm)		
Depth, Overall (in.) (incl. handles & bumpers)	36 1/16 (916 mm)		
Height, Overall (in.) (incl. 1 3/8" plate casters)	31 3/4 (806 mm)		
No. of Drawers	2		
No. of Half Doors	1		
Interior Depth (in.) (above condenser)	30 (762 mm)		
Interior Height (in.) (above condenser)	12 1/2 (318 mm)		
Interior Width (in.) (above condenser)	17 (432 mm)		
REFRIGERANT DATA			
Condensing Unit Size (H.P.)	1/3		
Capacity (BTU/Hr)*	1340		
ELECTRICAL DATA			
Voltage (int'l)	115/60/1 (220/50/1)		
Fans	2		
Total Amps (int'l)	6.1 (3.7)		
10 ft. Cord/Plug [attached] (int'l)	Yes (No)		
SHIPPING DATA			
Weight (lbs.)	340 (154 kg)		
Height - Crated (in.)	43 3/4 (1111 mm)		
Width - Crated (in.)	45 (1143 mm)		
Depth - Crated (in.)	47 (1194 mm)		
DRAWER PAN CONFIGURATIONS			

DRAWER PAN CONFIGURATIONS

Two Tier: (2) 12 x 20 x 4 pans (top) and (2) 12 x 20 x 6 pans (bottom)

Three Tier: (1) $12 \times 20 \times 4$ pan (top) and (2) $12 \times 20 \times 4$ pans per drawer (center & bottom)

* Rating @ -15°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.





Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







