

Project Name: _____ AIA#: _____

Model #: _____ Location: _____

SIS#: _____ Item #: _____ Quantity: _____



Gas Floor Fryer

15.5" Wide | 4 Tubes — 120,000 BTU | 50 lb. Oil Capacity

**50 pound oil capacity,
perfect for mid to high
volume basket frying,**

*with fast recovery for breaded/battered
product. An extension of Globe's gas
countertop cooking line — quality design,
durability, performance and price!*



Models

- GFF50G - Natural Gas Model (pictured)
- GFF50PG - Liquid Propane Model

Standard Features

- Stainless steel fully peened fry tank with smooth, polished welds
- Large foam zone, prevents excessive moisture in the oil which can adversely affect flavor
- Efficient 576 sq. inches BTU heat exchanger tubes
- Rugged cast iron burners 30,000 BTUs per tube
- Specialty high heat baffles inside the heat tubes for improved heating efficiency
- Robertshaw® millivolt gas valve and thermostat — 200-400 degrees
- 1-1/4" full ball-type port drain — with extension pipe for quick and easy cleaning
- Large cold zone prolongs oil life, prevents food particle carbonization
- High limit thermostat, with auto gas supply shut-off
- Sturdy 2.5" dia. 6" adjustable stainless steel legs — **one set of 4 casters included!**
- Heavy-duty stainless steel double rod basket hangers
- Stainless steel front and door with integral liner, galvanized sides
- Full length door rod and fully welded door magnet
- Includes twin nickel chrome wire mesh fry baskets with plastic coated handles (13.625" x 6.5" x 5.75" ea.)
- Includes drain extension pipe, basket support rack, stainless steel legs, set of 4 casters

Warranty


- Two years parts and labor
- Two years tank — full fryer replacement

Optional Accessories

- GFFBASKET3550 - Regular & large fry baskets
- GFFCOVER3550 - Fryer cover
- GFFCLEANSET - Fryer cleaning set
- GFFCONNECT3550 - Connecting strips
- GFFCASTERS - set of 4 casters



Approved by: _____ Date: _____



For indoor commercial use only.

DIMENSIONS | SPECIFICATIONS | SHIPPING INFORMATION

Reinforced carton for shipping. Weight of carton included below, may vary from shipment to shipment. *Shipped on a pallet, freight class 85.*

Model	Dimensions						Cooking Area	Oil Capacity	No. Burners BTUs ea	Total BTUs	Net Wt	Ship Wt
	A Width	B Depth	C Height	D Legs Height	E Gas Inlet Height	F - Drain Valve Height From Floor						
GFF50G GFF50PG	15.5" (39 cm)	30.3" (77 cm)	47.2" (68 cm)	6" (15.24 cm)	7" (17.78 cm)	10.25" (26.04 cm)	14" x 14" (35.6 cm x 35.6 cm)	50 lbs (16 kg)	<u>4</u> 30,000	120,000	149 lbs (67.6 kg)	192 lbs (87 kg)

GAS REQUIREMENTS AND INFORMATION

- Natural gas or LP main supply required
- Conversion of unit from natural gas to LP must be completed by an authorized Globe servicer
- 3/4" standard pipe size I.D. connection
- With LP gas we recommend an additional gas regulator (owner supplied) be placed between fryer and gas tank
- Must be installed 6" from flammable surfaces

OPTIONAL ACCESSORIES

- GFFBASKET3550 - 1 Large fry basket
- GFFCOVER3550 - Fryer cover
- GFFCLEANSET - Fryer cleaning set
- GFFCONNECT3550 - Connecting strips
- GFF-CASTERS - Set of 4 casters

Gas fryer has fully peened stainless steel fry tank with stainless steel front plate, door and frame. Large foam zone and 1-1/4" full ball-type port drain, with ample cold zone and built in flue deflector. Unit supplied with drain valve, drain extension pipe, 2 nickel chrome wire mesh fry baskets with plastic handles, 6" adjustable legs and set of 4 casters. Fryer has high performance cast iron burners, 4 totaling 120,000 BTUs, Robertshaw® thermostat, high heat limit with auto gas shut-off. Unit shall have a welded magnet for extra door support, galvanized sides, recessed handle and double rod stainless basket hanger. Fryer is CSA listed. Two-year tank warranty (full fryer replacement) and two-year parts and labor.