

WxDxH 23.4" x 24.5" x 31.5"

ADA Compliant 👃



HR24B 🛨









Dimensions / Capacity







One Section

HR24B

0 7 443

Interior Storage Capacity (CF) (AHAM)	3.7 ft ³
Overall Width x Depth	23.4" x 24.5"
Height	31.5"
Depth with Door Open at 90°	51.5"
Adjustable Shelves	3
Shelf Dimensions (W x D)	(1) 19.13" x 17", (2) 19.13 x 12"
Crated Weight	115 lbs.
Crated Shipping Dimensions (WxDxH)	26.8" x 24" x 36.6"
Electrical / Refrigeration	One Section HR24B
Voltage	115/60/1
HACR Breaker	15.0 Amps
Electrical Connection (NEMA)	5-15P 🛈
Voltage Range	104-127
Ambient Temp. Range	61° to 86°F
Control Setpoint Range	34° to 52°F
Amperage	1.15
Energy Consumption (kWh/day) @ASHRAE	0.51
Heat Rejection (BTU/Hr.) @NSF	145
Heat Rejection (BTU/Hr.) @NSF Approx. Nominal Compres. BTU/HR (HP)	145 501 (1/12HP)

Options	Warranty
	* 3 Year - parts and

☐ Glass Shelves

Printed in the U.S.A.

Refrigerant (charge amount, oz.)

Labor on entire machine.

R600a (1.33 oz.)

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Item #:		
Project:		
Qty:		
AIA#:		

Features


- Stainless steel exterior front, sides and top
- UL approved for outdoor use
- Interior LED lighting
- Energy efficient, one piece ABS interior liner
- Stainless steel exterior door with aluminum interior comes standard with locks
- Field reversible door
- Magnetic door gasket is easily removable for cleaning
- · Environmentally friendly insulation
- Electronic controls with LED Temperature Display and Audio/Visual Alarm
- High and low temperature alarms as well as "Door Open" alarm
- · Automatic time-initiated defrost
- (3) Epoxy coated shelves standard
- · Built-in cabinet installation with louvered trim
- Trim pieces included (see reverse)
- . 6 ft. cord and 5-15P NEMA plug
- · Three year parts and labor warranty


Hoshizaki reserves the right to change specifications without notice.





FRONT VIEW BACK VIEW inch [mm]





PLAN VIEW

TOP TRIM PANEL

