



Project: _____

Location: _____

Item #: _____ **Quantity:** _____

Model #: _____

MODEL: IRR-AGB96RI

REACH-IN: Top Mounted Reach-in Refrigerators - Roll-In.



General Strengths

- ✓ **Doors.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in. Doors are field reversible.
- ✓ **Control systems.** Higher precision in managing temperature settings. Greater ability to adjust of temperature ranges as per the end user's requirement.
- ✓ **100% Tested.** All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)

MODEL	Dimensions (inches) (mm)			Nº Door	Nº Shelves	Ref.	Ref. Weight (Lbs.) (gr.)	Temp. Range (°F) (°C)	Capacity (Cu. Ft.) (L)	Cond. Unit. H.P.	Case Amps 115V.	Crated Weight (Lbs.) (Kg.)
	W	D	H									
IRR-AGB96RI	71-5/8 1820	41-3/4 1060	93 2360	2	-	R134a	0.88 400	33°F/38°F 0°C/4°C	96.3 2726	3/4	9.9	507 229

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE



Infrico USA Corp.
7042 N.W. 46th
Street
Miami, FL 33166
1.305.777.9599
Office
1.305.777.9598 Fax

www.infrico.us
service@infrico.com

sales@infrico.com

— — — — —

