

Model:	Item #:	Date:
	·	

## **Gas Connector Complete Kit**

**Gas Connectors** 



## **Standard Features**

The Krowne Metal Gas Connector is a stainless steel hose designed to be used with stationary and caster-mounted commercial kitchen equipment. It's design is convenient for equipment that is routinely moved for cleaning as features such as the rotational end pieces and the included restraining cable provide both ease and durability when moving large gas-supplied equipment.

The green antimicrobial PVC-coated protective layer allows for easy cleaning while the stainless steel corrugated tubing provides both flexibility and a strong internal structure that will last with enduring strength.

- Ends rotate for simple installation and durability
- Heavy duty stainless steel corrugated tubing flexibility for easy installation
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability

## Includes:

No.	Name	Description
1	Gas Connector	Designed for moveable caster- mounted kitchen equipment.
2	Quick Disconnect	Easily disconnects gas hose to move equipment for maintenance and cleaning.
3	Gas Valve	Required by code to allow manual shutoff within 6 ft. of appliance.
4	Restraining Cable Kit	Prevents hose from being pulled too far. Includes mounting hardware.
5	90° Elbows	Gives versatility during installation (qty 2 included).

Visit krowne.com for complete replacement parts.

## **Product Compliance**

- ANSI Z21.41-2014 CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 CSA 6.16a-2012 Addenda
- Restraining Kits are required by law for all moveable gas equipment

Model No.	Interior Size	Length	BTU/hr
M5024K	1/2"	24"	87K
M5036K	1/2"	36"	77K
M5048K	1/2"	48"	68K
M5060K	1/2"	60"	60K
M5072K	1/2"	72"	55K
M7524K	3/4"	24"	232K
M7536K	3/4"	36"	218K
M7548K	3/4"	48"	180K
M7560K	3/4"	60"	158K
M7572K	3/4"	72"	139K
M10024K	1"	24"	414K
M10036K	1"	36"	379K
M10048K	1"	48"	334K
M10060K	1"	60"	294K
M10072K	1"	72"	279K
M12524K	1-1/4"	24"	699K
M12536K	1-1/4"	36"	615K
M12548K	1-1/4"	48"	541K
M12560K	1-1/4"	60"	476K
M12572K	1-1/4"	72"	419K

Ends rotate for simple installation and reduces strain on hose, enhancing durability	Green PVC-coating for protection with antimicrobial agent for easy cleaning	Heavy duty stainless steel radial wrap prevents hose from stretching	Stainless steel corrugated tubing built for flexibility and easy installation	Welded construction for added durability