

Project Name:_	
Location:	
ltem #:	
Otv:	

Maxx Ice Indoor Wine Cooler with Glass Door

MCWC28HC



ELECTRIC

120V / 60Hz / 1Ph Cord Length (Inches): 80 Plug Type: NEMA 5-15P Cord set included **NEMA 5-15P**



3RD PARTY APPROVALS





WARRANTY (USA / CANADA) -

1 Year Limited Warranty

Contact Maxx Ice at TechnicalServices@TheLegacyCompanies.com or 877.368.2797

The perfect addition to any indoor commercial entertainment space, the Maxx Ice Indoor Wine Cooler with Glass Door is an attractive way to store wine and other beverages. This wine cooler will complement any space with an exterior finish in black painted steel and a full-length glass door.

FEATURES AND CONSTRUCTION -

- 3 cu ft capacity
- Energy efficient interior LED lighting illuminates your wine bottles and lets you toggle between white and blue light
- 6 curved metallic wire bottle racks securely hold 28 bottles of wine
- Glass door lets you easily view your collection
- Holding temperature of 46°F to 64°F is ideal for both red and white wines
- Exterior finish in black painted steel with stainless steel handle complements any space
- Easy-to-clean, low maintenance ABS interior
- Adjustable leveling feet
- Electronic control panel with easy-to-read LCD digital display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed

STORAGE CAPACITY -

Cubic Feet: 3 cu. ft.

TEMPERATURE –

Temperature Range (Fahrenheit): 46° - 64°

Digital control system maintains optimum temperature This unit is designed to store pre-chilled product at the ideal serving temperature and is not intended to perform as a pull down refrigerator


These models are designed to operate in an environment where temperature and humidity do not exceed 75°F (24°C) and 55% relative humidity




Maxx Ice Indoor Wine Cooler with Glass Door

MCWC28HC


FRONT VIEW



SIDE VIEW



TOP VIEW



Temperature Range	Bottle Racks	Bottle Capacity	Amps	Refrigerant Type	Assembled Dimensions (L x W x H in)	Item Weight (Ibs)	Shipping Weight (lbs)
46° - 64°	6	28 Bottles	2.0A	R-134a	23" x 14.5" x 33.5"	77.0	96.0

INSTALLATION -

- A minimum clearance of 1/4" on the sides, 1/2" in the rear and 1" on top is recommended to promote adequate cooling air circulation
- Minimum cutout size for undercounter installation is 15" x 33.75"

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this document are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.