www.norlake.com



## ADVANTEDGE™ BOTTLE COOLERS



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

## SPECIFICATIONS FOR: NLBC50, NLBC65, NLBC80 & NLBC95

Finish: Black vinyl coated steel cabinet exterior front, sides and back with stainless steel top and sliding covers. Interior galvanized walls and stainless steel floor with floor drain.

Foamed-in-place with 1-1/2" CFC free polyurethane insulation. Insulation:

Standard with removable bottle opener cap catcher, integrated glass rail on rear Hardware:

> top, easy glide sliding lids with locks. Adjustable product dividers supplied. Plastic breaker strips around door openings to limit the formation of any condensation.

115 volt, 60 Hz, 1 phase with cord and NEMA 5-15P plug. ■ Electrical:

Self-contained forced air R-134a capillary tube refrigeration system. Automatic Refrigeration:

defrost and condensate evaporator requires no plumbing. Adjustable temperature

control with temperature range: +34°F to +38°F.

UL, C-UL Safety and ETL Sanitation (US & Canada) \*\* Approvals:

## STANDARD FEATURES


- Adjustable temperature control
- Air cooled condensing unit
- Automatic defrost and condensate evaporator
- Black vinyl coated steel exterior
- Capillary tube system
- Durable galvanized interior walls
- Removable cap catcher
- Multiple evaporator fan motors


- Stainless steel top with integrated glass rail
- Stainless steel interior floor
- Stainless steel sliding lids with locks
- Temperature range: +34°F to +38°F
- Vinvl coated product dividers
- UL, C-UL Safety and ETL Sanitation (US & Canada) \*\*
- Warranties: 3 year parts & labor, 5 year compressor


## OPTIONAL FEATURES\*


- Additional dividers
- 4" plate casters

**SPECIFICATION** GUIDE










FRONT NLBC65


TOP NLBC65

FRONT NLBC50


TOP NLBC50




TOP NLBC80



FRONT NLBC80



**TOP** NLBC95




FRONT NLBC95

			SPECIFICATIONS	
Models	NLBC50	NLBC65	NLBC80	NLBC95
Crated Weight (lbs) (kg)	260 (118)	310 (141)	415 (188)	430 (195)
Crated Height (in) (cm)	41 (104)	41 (104)	41 (104)	41 (104)
Crated Width (in) (cm)	52-1/2 (133)	67 (170)	83 (211)	97-1/2 (248)
Crated Depth (in) (cm)	29-1/8 (74)	29-1/8 (74)	29-1/8 (74)	29-1/8 (74)
Interior Height (in) (cm)	27-7/8 (71)	27-7/8 (71)	27-7/8 (71)	27-7/8 (71)
Interior Width (in) (cm)	46 (117)	60-1/2 (154)	76-1/2 (194)	91 (231)
Interior Depth (in) (cm)	22-3/4 (58)	22-3/4 (58)	22-3/4 (58)	22-3/4 (58)
Overall Height (in) (cm)	33-1/2 (85)	33-1/2 (85)	33-1/2 (85)	33-1/2 (85)
Overall Width (in) (cm)	50 (127)	64-1/2 (164)	80-1/2 (205)	95 (241)
Overall Depth (in) (cm)	28-1/2 (72)	28-1/2 (72)	28-1/2 (72)	28-1/2 (72)
Gross Cubage (CuFt) (L)	14.8 (419)	20.1 (569)	26 (736)	31.3 (886)
Number of Dividers	3	4	5	6
Condensing Unit Size	3/8 HP	3/8 HP	3/8 HP	3/8 HP
Refrigerant	R-134a	R-134a	R-134a	R-134a
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes	Yes
NEMA Plug Configuration	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	6.1	6.1	6.1	6.1
12 oz. Can Capacity	857	1191	1575	1893
12 oz. Bottle Capacity	377	539	715	877

Specifications subject to change without notice.

<sup>\*</sup> Floor drain connection exits the rear of the cabinet condensing unit compartment.







Revision Date: 4/18 Part Number: 143469

SIDE VIEW ALL MODELS

©2018 Nor-Lake, Inc. A division of Standex International Corp. All rights reserved.
Printed in the USA.