www.norlake.com



# **CURVED LID DISPLAY FREEZER**



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

## SPECIFICATIONS FOR: CTB31-6, CTB43-9, CTB52-12, CTB71-17

Painted white powder coated steel interior and exterior Finish:

Doors: Sliding glass doors - curved glass with one piece frame, lid locks with keys Hardware: (4) four casters, baskets and dividers, rubber bumper guards on grill side

Electrical: 115/60/1 with cord and plug

Refrigeration: Self-contained refrigeration system. Operating temperature: -18°F to +10°F.

R290 Refrigerant.

ETL Safety (US and Canada), ETL Sanitation Approvals:


#### STANDARD FEATURES


- Baskets and dividers
- Bottom drain with plug
- External analog thermometer display
- Interior LED lighting with separate on/off switch
- Lid lock and keys
- Operating temperature: -18°F to +10°F
- Power indicator light
- Rubber bumper guards on grill side
- Sliding glass doors
- White interior and exterior
- Warranties: 1 year parts and labor
- Approvals: ETL Safety (US and Canada), ETL Sanitation
- \* Most options are available one week from receipt of order. Please contact us for specific questions.
- \*\* ETL is Intertek Labs Safety Certification Mark which indicates that Intertek has tested the equipment to applicable CSA Standards. \*\* ETL-Sanitation is Intertek Labs Sanitation Certification Mark which indicates that Intertek has tested the equipment to applicable NSF Standards.

### **OPTIONAL FEATURES \***

Basket dividers







### **SPECIFICATIONS**

O LON TOATION				
Models	CTB31-6	CTB43-9	CTB52-12	CTB71-17
Crated Weight (lbs) (kg)	155 (70)	188 (85)	212 (95)	270 (122)
Crated Height (in) (cm)	40 (102)	40 (102)	40 (102)	40 (102)
Crated Width (in) (cm)	33 (84)	43 (109)	52 (132)	69-1/2 (177)
Crated Depth (in) (cm)	30-1/2 (77)	30-1/2 (77)	30-1/2 (77)	30-1/2 (77)
Interior Height (in) (cm)	21 (53)	21 (53)	21 (53)	21 (53)
Interior Width (in) (cm)	25-7/8 (66)	35-3/8 (90)	43-1/4 (110)	60-7/8 (155)
Interior Depth (in) (cm)	21-1/2 (55)	21-1/2 (55)	21-1/2 (55)	21-1/2 (55)
Overall Height (in) (cm)	33-1/2 (85)	33-1/2 (85)	33-1/2 (85)	33-1/2 (85)
Overall Width (in) (cm)	31 (79)	41 (104)	49 (125)	66-1/2 (169)
Overall Depth (in) (cm)	27-3/8 (70)	27-3/8 (70)	27-3/8 (70)	27-3/8 (70)
Gross Cubage (CuFt) (L)	8.3 (234.9)	11.5 (325.5)	14.5 (410.4)	20.5 (580.2)
Number of Baskets*	3	4	5	6
Number of Casters	4	4	4	4
Condensing Unit Size	1/3 HP	3/8 HP	3/8 HP	3/4 HP
Refrigerant	R290	R290	R290	R290
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes	Yes
NEMA Plug Configuration	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	1.0	1.2	1.5	2.8

Specifications subject to change without notice.





<sup>\*</sup> includes 1 divider per basket