

# **PFC**

## SEMI-AUTOMATIC VENTLESS ELECTRIC COUNTERTOP DEEP FRYER

## **KEY FEATURES**

- Integral ventless design
- Built-in fire suppression
- Hepa style air filtration
- Large output
- Small footprint
- Odorless
- Easy to clean

## **TOUCH CONTROL**


- Cook time sensitivity (CTS)™
- Preset counters
- Food type sensitivity (FTS)™
- Stand by mode
- Hold time monitor







The Benchmark in Ventless Deep Frying



#### **OPTIONS & ACCESSORIES**

- **PERFECT FILTER KIT** Includes: (1) Oil Filter unit, (1) hand held oil tester w/ wall mount, & (100) disposable filter pads
- LOCKING DOOR LATCHES Employee safe guard (must specify on order)
- AIR FILTER REPLACEMENT KIT Includes: (1) replacement air filter
- FIRE ALARM SIGNAL INTEGRATION
- EXTRA LARGE BASKET 5"H x 10"W x 7"D
- BASKET COVER/SUBMERGER SCREEN
- WIFI/CLOUD CONNECTIVITY Optional wifi module to connect to Open Kitchen, allowing remote access and data acquisition.
- Open Kitchen SAP (Secure Access Point)

### **COOKING CAPACITY**

Oil Capacity 2 US Gallons (8 L)
Product Capacity 3 lb per load (1.3 kg)

#### **WEIGHTS & SHIPPING**

Product Weight 106 lbs (48.08 kg)
Shipping Weight 130 lbs (58.96 kg)
Shipping Dimensions Depth 17.95" (456 mm)

Width 17.94" (556 mm) Height 27.07" (688 mm)

Shipping Cube 7.56 ft3 (.214 m3)

## **CLEARANCES**

Sides	1" (25.4mm)	
Back	2" (50.8mm)	
Тор	0" (0mm)	

## **ELECTRICAL SPECIFICATIONS**

MODEL	VAC	KW	CYCLE	PHASE	AMP	NEMA	
PFC500 208	5.0	60	1	24	6-30P		
			3	14	15-30P		
PFC730	7.3	60	1	35	6-50P		
		7.5	00	3	21	15-30P	
PFC500	240	5.5	50/60	1	23	6-30P	
				3	14	15-30P	
PFC730		8.0	50/60	1	34	6-50P	
				3	20	15-30P	
PFC500	200	4.7	50/60	1	24	6-30P	
PFC730		6.8		1	34	6-50P	
PFC500	220	4.6	50/60	1	21	6-30P	
PFC730		6.7		1	31	6-50P	
PFC500	230	5.0	50/60	1	22	6-30P	
PFC730		7.3		1	32	6-50P	
PFC500	220/380	4.6	50/60	3	7	*	
PFC730		6.7		3	11	*	
PFC500	230/400	5.0	50/60	3	8	*	
PFC730		7.3		3	11	*	
PFC500	240/415	5.5	50/60	3	8	*	
PFC730		8.0		3	12	*	
* No plug supplied. 1 Phase: Cord only   3 Phase: No cord or plug							

For use on an individual branch circuit. Fryer must be properly connected to a grounded, dedicated phase circuit according to local standards and codes.

#### \*Cord Set Standard

## **BASKET OPTIONS**

Optional Basket Cover

Extra Large Basket 5" H x 10" W x 7" D







PERFECT FRY™
PORTABLE OIL FILTER