robot @ coupe°

20 to 100 portions

8 to 44 lbs

Blixer® 30



E	PRODUCT FEATURES	/ BENEFITS

MOTOR BASE

Number of 7 oz

Quantity processed per

portions:

operation

- Induction direct drive motor for intensive use.
- Power 7 HP.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- 2 speeds: 1800 and 3600 rpm.
- Pulse function for a better cut precision.

CUTTER FUNCTION

- Removable and tiltable 28 L bowl for effortless emptying and cleaning.
- Bowl-base blade assembly with 2 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Stainless-steel construction for making cleaning easier.
- Timer from 0 to 15 minutes for a better preparation control.
- Transparent lid with bowl scraper to improve the end-product consistency and with a lid wiper to enable user to monitor processing.
- Opening in center of lid for adding liquid or dry ingredients during processing.
- 3 retractable wheels making it easier to move the appliance in order to clean the surface.

INCLUDED ACCESSORIES

- 2 stainless steel fine serrated blade assembly
- Scraper arm and lid wiper
- 3 retractable wheels

SALES FEATURES

Blixer 30 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

TECHNICAL FEATURES

Blixer 30. 3-phase. Power 7 HP. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 28 L stainless-steel bowl. Bowl-base blade assembly with 2 detachable and height-adjustable fine serrated blades included. 20 to 100 portions (7 oz.) and more.

Select your options at the back page, F part.

C TEC	HNICAL DATA	
Output power	7 HP	
Electrical data	208-240V/60/3	
Speeds	1800 and 3600 rpm	
Dimensions (WxDxH)	27 3/8" × 23 5/8" × 48 1/16" - Cube: 29.33	
Rate of recyclability	95%	
Net weight	323 lbs	
Nema #	L15-30P	
Reference	BLIXER 30 A - 208-240V/60/3	

STANDARDS

ETL electrical and sanitation Listed/cETL (Canada)



Update: October 2017

Specification sheet

www.robotcoupeusa.com

Slixer® 3(



Blixer® 30

F OPTIONAL ATTACHMENTS

- Fine serrated edge stainless steel "S" Blade Ref. 57076
- Complete Bowl Assembly Ref. 59132

G ELECTRICAL DATA 208-240V/60/3 – delivered with cord and plug.







