

CL60 Pusher Feed Head



OPTIONAL
+
50
DISCS

**Dicing and
French Fries
capability**



A SALES FEATURES

CL 60 Pusher Feed Head is ideal for slicing, ripple cutting, grating, dicing, shredding and making french fries from all types of fruit and vegetables, as well as grating cheese, in very large quantities.

B TECHNICAL FEATURES

CL60 Pusher Feed Head – Three-phase. Power - 3HP. 2 speeds 425 and 850 rpm. Magnetic safety system, motor brake and lever-activated auto restart. This metal Vegetable Preparation Machine has a lateral ejection facility and is equipped with 2 hoppers: 1 XL full moon hopper, diameter: diameter 7", and integrated tube Ø 2 1/4" and/or Ø 1,5". Stainless steel motor base and chute. This model is equipped with with 2 wheels and a handle for easy movement. D-Clean Kit. Suitable for up to 3000 covers per service. Included: 28064W (3mm) 1/8" slicing disc and 28058W (3mm) 1/8" grating disc and 2 disc racks. Large range of 52 Mineral+ discs available as option: easy cleaning, dishwasher resistant.

Select your options at the back page, **F** part.

C TECHNICAL DATA

Output power	3HP
Electrical data	Three phase - 8.3 Amp
Speeds	425 and 850 rpm
Dimensions (HxLxW)	45" x 24" x 16"
Rate of recyclability	95%
Net weight	154 lbs
Nema #	L15 - 20P
Reference	CL 60 Pusher Series E 208-240V/60/3

D

**Number of meals
per service**

300 to 3000

**Theoretical output
per hour***

3970 lbs

E

PRODUCT FEATURES / BENEFITS

MOTOR BASE

- Industrial induction motor for intensive use.
- Power - 3HP
- Stainless steel motor base and shaft.
- Magnetic safety system with motor brake and lever-activated auto restart.
- 2 Speeds 425 and 850 rpm

VEGETABLE PREPARATION FUNCTION

- Vegetable Preparation Machine equipped with 2 hoppers: 1 XL full moon hopper to accommodate a whole cabbage or up to 15 tomatoes and 1 cylindrical hopper for long, delicate vegetables. Exactitude pusher: reduction of tube diameter to cut up small ingredients.
- Removable continuous feed lead. Tilting of the feed heads in line with the motor base for space-saving.
- Reversible discharge plate for processing delicate produce.
- Lateral ejection facility for greater user comfort.
- Optimum size and height. CL60 is equipped with 2 wheels and a handle, guaranteeing very easy movement.
- Lever-activated auto restart (by the pusher)
- Lever-assisted facility requires less effort from the operator and increases output.
- Vertical pusher pressure exerted on vegetables to ensure uniform cuts.
- Large range of 52 Mineral+ discs available as option: easy cleaning, dishwasher resistant.
- Included: 28064W (3mm) 1/8" slicing disc and 28058W (3mm) 1/8" grating disc and 2 disc racks.
- Stainless steel blades on slicing discs, blades on Julienne discs and grating discs are removable.
- 3 positions for optimum operator comfort. Lever-activated auto restart.
- Brush to facilitate cleaning of motor shaft.
- D-Clean Kit to facilitate cleaning of dicing grids.

MASHED POTATO FUNCTION

- option: Mashed Potato Kit

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



* Results may differ depending on the type of the hopper used, the choice of the cut and the setup of the workstation.

Specification sheet

www.robot-coupe.com

Update: May 2024

Robot Coupe USA, Inc.

264 South Perkins - Ridgeland, MS 39157

PH: 601-898-8411 - Toll free: 800-824-1646 - Fax: 601-898-9134

info@robotcoupeusa.com

CL60 Pusher Feed Head

F

OPTIONAL ACCESSORIES

- Automatic Feed Head - Ref. 39681
- 4 tubes Feed Head: Special long vegetables - Ref. 28162
- Straight and bias cut hole hopper: for long vegetables and bias cuts - Ref. 28157
- EasyClean Xpress 8x8mm - Ref. 49305
- EasyClean Xpress 10x10mm - Ref. 49309
- EasyClean Xpress 12x12mm - Ref. 49313
- EasyClean Xpress 14x14mm - Ref. 49314
- Wall 8-disc holder - Ref. 107812
- Motor shaft brush - Ref. 49257
- 3 mm potato ricer equipment - Ref. 28208

SUGGESTED PACKS OF DISCS

3 disc package	5mm (3/16") coarse grating, 6mm (1/4"x 1/4") julienne and 5mm (3/16") slicing discs.
5 disc package	5mm (3/16") coarse grating; 6mm (1/4"x1/4") julienne; 5mm (3/16"), 10mm (3/8") slicing discs; 10x10mm (3/8" x 3/8") dicing grid
16 disc package	Slicers - 0.8mm (1/32"), 2mm (5/64") & 5mm (3/16"). 2 graters - 2mm (5/64") & 5mm (3/16"); 3 dicing - 5x5x5mm (3/16"), 10x10x10mm (3/8") & 14x14x5mm (9/16"x9/16"x3/16"). 2 Julienne sticks - 2.5 x 2.5mm (1/10"x1/10") & 2 x 10mm (5/64"x3/8"). D-Clean Kit and 2 disc holders.



SLICERS

0.6 mm	28166W
0.8 mm	28069W
1 mm (1/32")	28062W
2 mm (5/64")	28063W
3 mm (1/8")	28064W
4 mm (5/32")	28004W
5 mm (3/16")	28065W
6 mm (1/4")	28196W
8 mm (5/16")	28066W
10 mm (3/8")	28067W
14 mm (9/16")	28068W
20 mm (25/32")	28132W
25 mm (1")	28133W
cooked potatoes 4 mm (5/32")	27244W
cooked potatoes 6 mm (1/4")	27245W



RIPPLE CUTTING

2 mm (5/64")	27068W
3 mm (1/8")	27069W
5 mm (3/16")	27070W




GRATERS

1.5 mm (1/16")	28056W
2 mm (5/64")	28057W
3 mm (1/8")	28058W
4 mm (5/32")	28136W
5 mm (3/16")	28163W
7 mm (9/32")	28164W
9 mm (11/32")	28165W
Röstis potatoes	27164W
Raw potatoes	27219W
Fine Pulping disc	28055W
Hard Cheese grate	28061W



JULIENNE

1x8 mm tagliatelle (1/32"x5/16")	28172W
1x26 onion/cabbage (1/32"x1 1/4")	28153W
2x2 mm (5/64" x 5/64")	28051W
2x4 mm (5/64" x 5/32")	27072W
2x6 mm (5/64" x 1/4")	27066W
2x8 mm (5/64" x 5/16")	27067W
2x10 tagliatelle (5/64"x3/8")	28173W
2.5x2.5 mm (1/10" x 1/10")	28195W
3x3 mm (1/8" x 1/8")	28101W
4x4 mm (5/32" x 5/32")	28052W
6x6 mm (1/4" x 1/4")	28053W
8x8 mm (5/16" x 5/16")	28054W



DICING EQUIPMENT

5x5 mm (3/16")	28110W
8x8 mm (5/16")	28111W
10x10 mm (3/8")	28112W
12x12 mm (15/32")	28197W
14x14x5 mm Mozzarella (9/16"x9/16"x3/16")	28181W
14x14x10mm (9/16"x9/16"x3/8")	28179W
14x14 mm (9/16")	28113W
20x20 mm (25/32")	28114W
25x25 mm (1")	28115W
2" Lettuce Cut	28180W



FRENCH FRY EQUIPMENT

8x8 mm (5/16" x 5/16")	28134W
8x16 mm (5/16" x 5/8")	28159W
10x10 mm (3/8" x 3/8")	28135W
10x16 mm (3/8" x 5/8")	28158W

G

ELECTRICAL DATA

208-240V/60/3 - delivered with cord and plug.

