

COMBI VEGETABLE PREP.-CUTTER CK-35V 120/50-60/1

2 in 1: vegetable cutter (1000 lb) + cutter with 5.5 liter bowl.



seconds and in a standardized way: dense texture, fine texture, pulses (PrecisePulse function).

✓ Option to customize programs for recipe standardization.

Built to last

Made from stainless steel and food-grade materials of the highest quality: stainless steel motor block and food-grade aluminium head. Stainless steel hopper with highly-resistant lid.

Maximum comfort for the user

- Ergonomic design: product sliced in one single movement.
- √ Lateral product output: it requires less room on the work surface and directs the product avoiding splashing.
- Advanced control panel that is very intuitive to use and offers all the information at a glance.

Maintenance, safety, hygiene

- ✓ Plunger, lid and bowl easy to remove for changing or cleaning.
- √ Combination of security systems: head, covers, bowl, power switch.
- Appliance certified by NSF International (regulations on hygiene, cleaning and materials suitable for contact with foods).
- √ 100% tested.

SALES DESCRIPTION

It has a variable speed motor block, universal head and 5.5 I cutter bowl equipped with a rotor with micro-serrated blades.

"Brushless" technology.

Equipped with "brushless" technology: powerful and efficient motors.

- ✓ Maximum efficiency: maintain the torque throughout the speed range.
- Exclusive "force control system": guarantee of a uniform and high quality result.
- Lightweight and compact design: they weigh less, they occupy less space.
- √ Improved air/water-tightness since no ventilation is required.
- ✓ They generate less noise: improved workplace environment.

Cutting function: a perfect cut

- High precision settings and comprehensive cutter and disc design aimed at obtaining a perfect cut.
- It can be fitted with a wide range of discs and grids of the highest cutting quality. By combining these accessories, you can achieve more than 70 different types of cuts and grating grades.
- Exclusive "Force Control System" to optimise and standardise the cutting of each product: acoustic warning when the motor exceeds the pre-established force.

Cutter function: efficiency and performance

- √ Possibility of programming by time and pulse button.
- √ Reverse function, ideal for mixing products instead of cutting.
- √ 5.5 It stainless steel bowl.
- √ Transparent lid with built-in "cut&mix" mixer.
- Depending on the purpose, the possibility of using optional smooth or perforated blades.

INCLUDES

- √ Variable speed motor block.
- √ Universal head.
- Cutter bowl, with micro-serrated blade rotor.
- √ Universal grid cleaner QC-U.

OPTIONS

- Tube head.
- ☐ Discs, grids and disc support.
- ☐ Rotor with smooth cutting blades.
- Rotor with perforated cutting blades.
- Support-trolley.
- ☐ Grid cleaning kit.

Accessories

- ☐ FCC curved slicing discs
- ☐ FCO rippled slicing discs
- FFC chipping grids
- ☐ FMC dicing grids
- ☐ FCE julienne discs
- ☐ FR shredding & grating discs
- Disc and grid packs Heavy Duty
- Disc and grid holder
- □ Blades for CK / K / KE
- ☐ Quick Cleaner: grid cleaners☐ FC-D slicing discs
- ☐ SH shredding & grating discs

SPECIFICATIONS

Total loading: 3 Hp

Electrical supply: 120 V / 60 Hz / 1~ (15 A)

Plug: USA (NEMA 5-15P / 2P+G)

As vegetable preparation machine

Hourly production: 200 lb - 1000 lb

Inlet opening: 21 in²

Disc diameter: 8"

Speed as veg. slicer: 300 - 1000 rpm

External dimensions (W x D x H): 15.4" x 16.1" x 21.7"













COMBI VEGETABLE PREP.-CUTTER CK-35V 120/50-60/1

2 in 1: vegetable cutter (1000 lb) + cutter with 5.5 liter bowl.

P/N. 1050756

Net weight (Veg.Prep.): 53 lb


As cutter


Bowl capacity: 5.8 qt Speeds as cutter (positions): 300 - 3000 rpm External dimensions (W x D x H):11.3" x 15.2" x 19.2" Net weight (Cutter): 39.7 lb


Noise level (1m.): <70 dB(A)


Background noise: 32 dB(A)

Crated dimensions 27.8 x 16.3 x 20.3 " Volume Packed: 0.15 m³ Gross weight: 70.1 lbs.











usa@sammic.com 1225 Hartrey Avenue 60202-1056 Evanston, IL phone +1 (224) 307-2232 toll free +1 844 275 3848



Project	Date
Item	Qty

Approved