



RB PRINTER FOR SU VACUUM PACKING MACHINES (USA)



P/N. 1140569

SPECIFICATIONS

Electrical supply: 120 V / 50-60 Hz / 1~
Plug: USA (NEMA 5-15P / 2P+G)

Crated dimensions

8.7 x 14.0 x 10.2 "
Gross weight: 6.6 lbs.



SALES DESCRIPTION

Direct thermal or thermal transfer printer for printing labels.
Specially configured for Sammic SU vacuum packing machines, interface USB-RS232C, to print labels directly from the vacuum packing machine.

- ✓ Print method: Direct thermal / Thermal transfer.
- ✓ Thermal transfer method is indicated for sous-vide cooking, as thermal transfer labels stand up to 212°F during the cooking process.
- ✓ 203 dpi resolution.
- ✓ 8 MB flash memory.
- ✓ Print speed: 127 mm/s. - 5 inch per second.
- ✓ Code page support.
- ✓ Emulation options.
- ✓ User-friendly. Easy maintenance.

OPTIONAL

- ☐ 1140566 Direct thermal labels. ☐ 1140567 Thermal transfer labels.



sammic | www.sammic.us
Food Service Equipment Manufacturer

usa@sammic.com phone +1 (224) 307-2232
1225 Hartrey Avenue toll free +1 844 275 3848
60202-1056 Evanston, IL



Project

Date

Item

Qty

Approved

product sheet
updated 03/15/24

FOOD PRESERVATION AND SOUS-VIDE
ACCESSORIES - VACUUM PACKING MACHINES