VACUUM PACKING MACHINE SE-208 120/50-60/1

Tabletop model. 8 m³/h. Bar length: 280 mm.



√ NSF-listed model.

P/N. 1141081



- √ Sensor controls
- √ Up to 10 seconds of extra vacuum pull
- √ Soft air function
- √ Dry oil cycle

- √ BUSCH pump
- √ NSF approved
- √ Clear methacrylate lid
- √ Filling plate

OPTIONAL

- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and
- accessories
- Additional filling plates

SPECIFICATIONS

Pump capacity: 350 cf/h

Bar length: 11" Total loading: 0.6 Hp

Vacuum pressure (maximum): 2 mbar Electrical supply: 120 V / 60 Hz / 1~ (6.3 A) Plug: USA (NEMA 5-15P / 2P+G)

Internal dimensions

- √ Width: 11.3"
- ✓ Depth: 13"
- √ Height: 4.3"

External dimensions (W x D x H)

- √ Width: 13.2"
- ✓ Depth: 16.9"
- √ Height: 13"

Net weight: 71 lb

Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

Crated dimensions

15.7 x 20.7 x 15.4 " Gross weight: 77.2 lbs.



SALES DESCRIPTION

11" sealing bar. 350 cf/h Busch vacuum pump.

Vacuum controlled by sensor.


- ✓ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- Digital keyboard.
- √ Control panel equipped with display indicating the exact vacuum percentage.
- √ "Pause" button to marinate food.
- Safe liquid packing thanks to sensor control.
- ✓ Double seal.
- √ Cordless sealing bar.
- √ Bag-sealing programme.
- ✓ Pulse-controlled decompression.
- √ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid.
- Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.
- Safety system with protection against vacuum failure.











usa@sammic.com 1225 Hartrey Avenue 60202-1056 Evanston, IL phone +1 (224) 307-2232 toll free +1 844 275 3848



Project	Date
Item	Qty