



1000 WATTS



R21LVF

- 1.0 cu. ft. Capacity, with High Quality Stainless Steel Interior, Exterior, and Door
- Touch Controls: Provides 10 Programmable Memories with One-Second Increment Timing;
 Built-In Safeguards Prevent Unauthorized Changes
- Express Defrost™: Automatically Divides Total Defrosting Time into 3 Stages with 3 Power Levels
- Double Quantity Pad: Automatically Provides Optimum Heating Times for Two Portions for Excellent Results




FEATURES	
Finish	Stainless Steel
Grade	Medium Duty
Oven Control	Touch Pads with Braille
Capacity (cu. ft.)	1.0
Output Power (Watts)	1000
Power Levels	100%
Express Defrost™	Yes
Programmable	Yes, 10 Programmable
	Memories
Memory Check	Yes
Double Quantity	Yes
Display	Digital
Interior Light	Yes
Door Handle	Trigger Switch
Door, Cabinet, Interior	Stainless Steel
Door Window	See-Through


Cavity Dimensions (w x h x d)	13-7/8" x 8-1/8" x 14-5/8"
Product Dimensions (w x h x d)	20-1/2" x 12-1/8" x 16"
Product Weight / Shipping Weig	ht 37 lbs / 44 lbs
ADDITIONAL SPECIFICATIONS	
AC Power Required	120V, 60Hz, 1.6KW, 14A
NEMA Pagantagla	5-15R
NEMA Receptacle	- · · · · · · · · · · · · · · · · · · ·
UPC	074000616486

DIMENSIONS & WEIGHT (in. / lbs.)

FRONT VIEW 20.47"











Design and specifications subject to change without notice. Sharp is a registered trademark of Sharp Corporation. SelectaPower, SelectaTime and Express Defrost are trademarks of Sharp Corporation. All other trademarks are the property of their respected owners.

