

D '		
Pro	ect	٠
FIU	CUL	

Model # : Item # :

Qty :

Available W/H :

Approval :

Glass Half Door Heated Cabinet

PRO Series Model : PRO-77-6H-G

Reach-In

____ FEATURES & BENEFITS ____

Digital temperature control & monitor system Keep food products safe by maintaining constant temperatures.

- Alarm beeps when doors are not sealed.
- Early warning alarm program detects issues before malfunction occurs.
- Digital display allows for easy monitoring.
- Sensitive touch display.
- Ducted fan air distribution system Maintains temperature within the food zone
- On/Off switch

ON/OFF switch is located on control panel

All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a **22** gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving


Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

LED interior lighting

Includes a U.S. patented dimming option, exclusively from Turbo Air. This feature reduces energy consumption by 3~5%.

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Half length glass doors with locks
- Self-closing doors with stay open feature at 120 degrees
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles





* Depth does not include 1-1/4" for door handles. † Height does not include 5" for caster height.

Glass Half Door Heated Cabinet

Reach-In **PRO** Series

Model: PRO-77-6H-G

ELECTRICAL DATA	
Voltage	208/115/60/1
Plug Type	O NEMA L14-20P
Full Load Amperes	15
Wattage (W)	3000
Feed Wires with Ground	4
Cord Length (ft.)	8
DIMENSIONAL DATA	
# of Doors	6
# of Racks Accepted	3
Net Capacity (cu. ft.)	73.9
Ext. Length Overall (in.)	773/4 (1976mm)
Ext. Depth Overall (in.)*	337/8 (860mm)
Ext. Height Overall (in.) [†]	78 (1982mm)
Int. Length Overall (in.)	681/4 (1735mm)
Int. Depth Overall (in.)	275/8 (702mm)
Int. Height Overall (in.)	583/4 (1493mm)
# of Shelves	9
Shelf Size (L x D) (in.)	231/2 x 263/8 (Left/Right)
	25 x 263/8 (Middle)
Net Weight (lbs.)	660
Gross Weight (lbs.)	728

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1-1/4" for door handles.

† Height does not include 5" for caster height.

WARRANTY: 3 Year Parts and Labor Warranty

STANDARD FEATURES

- Door locks standard
- Standard 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES

- 5" caster, 1/2" diameter & 13 TPI:
- M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: (L, R) H50R901700, (M) H77R801710
- Half door bun tray rack: TSP-2224
- (each holds up to six 18"L x 26"D sheet pans)
- Tray slides kits: TS23-N1LR(#1), TS23-N4LR(#4), TS23-UNLR-H(Universal), TS3-N1C(#1), TS3-N4C(#4), TS3-UNC-H(Universal)

(GERMAN)


- (1) Pair of #1 Tray Slides: H26R104460
- (1) Pair of Universal Tray Slides: H26R104470

Ver.20200421



PLAN VIEW

(unit : inch)



351/8 (892mm) 337/8 (860mm) (mu (686r 27 78 (1982mm 591/2 (1510mm) 583/4 (1493mm) Ē 686 27 6 1

SIDE VIEW

Turbo Air: 800-627-0032 **GK**: 800-500-3519 ■ Warranty : 800-381-7770 ■ AC : 888-900-1002





Turbo air Texaking