

#### WE RAISE THE BAR. WE SET THE STANDARD.

Project Item Number Quantity

# Reversible Dough Sheeter

#### Models:

> SFG500T: Floor Model

> SFG500TM: Floor Model





## Features: • Reversible

Dough Sheeter

Univex Corporation

SFG500T/TM

Reversible dough sheeter

 Hand operation for thickness and foot pedal operation for carpet (left to right)

• 0 to 1.9" (4.8cm) adjustable cylinder, separation changes dough thickness

Hard chrome polished cylinders

• Tables fold upright for storage and movement

Powerful 3/4 hp motor

 Sheets dough onto rolling pins to allow for transport of rolled dough to work area

 Interlock switches protect operator from injury if safety guard is opened

Pivoting and removable arms

Convenient storage in base for rolling pins

#### Standard Accessories:

• Heavy duty rolling pins

Designated area for flour storage for use while sheeting

#### **Optional Accessory:**

• Hand operation for carpet (left to right) need to specify when ordering

#### Warranty:

One year, on-site parts and labor




Univex Corporation www.Univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249





### **Reversible Dough Sheeter**

### **SFG500T / TM**









Line drawing is the SFG500TM

	SFG500T	SFG500TM
Α	75.6" (192cm)	111.2" (282.5cm)
В	38.3" (97.3cm)	42.2" (107.2cm)
С	50" (127cm)	50" (127cm)

3-D View

Other Dimensions					
Model	Base Length	Belt Width	Length Folded	Height Folded	Carpet Length
SFG500T	29.625" (75.3cm)	19.75" (50.2cm)	29.625" (75.3cm)	58.375" (148.3cm)	27.625" (70.2cm)
SFG500TM	29.625" (75.3cm)	19.75" (50.2cm)	43.375" (110.2cm)	75.625" (192.3cm)	46.5" (118.1cm)

Controls: Main power switch, emergency stop switch and direction control lever and foot pedal for forward and reverse table directions.

Manually adjustable space between rolling cylinders adjusts in increments from 0" to 1.9" (0 to 4.8cm)

Drive: Chain drive

NEMA #: L-15-20

**Optional Voltage:** 

SFG500T & SFG500TM: 115/60/1 220/60/1 400/60/1 400/60/3

Electrical Information (60Hz)					
Model	Standard Voltage	Phase	hp(kW)	Amps	
SFG500T	220	3	0.75 (0.55)	2.60-7.35	
SFG500TM	220	3	0.75 (0.55)	2.60-7.35	

Shipping Information				
Model	Net Weight	Shipping Weight	Overall Dimensions	
SFG500T	375 lbs. (170Kg)	408 lbs. (185Kg)	61.4" (156cm) H x 36.6" (93cm) W x 55.9" (142cm) D	
SFG500TM	485 lbs. (220Kg)	518 lbs. (235Kg)	61.4" (156cm) H x 36.6" (93cm) W x 55.9" (142cm) D	



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249