

HEATED HOLDING**VULCAN****CBFT SERIES
HOLDING & TRANSPORT CABINET**

Model CBFT

**SPECIFICATIONS**

Vulcan Models CBFT and CBFTHS stainless steel cabinets with welded double pan construction. Support channels welded at base, integral dual layer fully welded corner posts. Continuous wraparound aluminum (dove-tail) designed bumper complete with (secure fit) non-marking vinyl insert. Double pan fully insulated door, 270 degree swing, 12 gauge hinges, recessed door pulls. Top mounted forced air heat, with rear mounted "tunnel" distribution system. Electronic thermostat/thermometer equipped with Lexan™ cover, lighted on/off switch. Super duty 5" polyurethane casters mounted to 1/4" mounting plates. (2) swivel casters with brakes, (2) rigid casters equipped with mounting plate secured to reinforced base channel with 3/8" bolts. All fasteners are tamper-proof, hinges and transport latches are 12 ga. and fully welded to the cabinet. Fully welded one piece shelving is removable for cleaning. Model CBFT holds twelve 18" x 26" x 1" bun pans or twenty-four 12" x 20" x 4" hotel pans. Model CBFTHS holds six 18" x 26" x 1" bun pans or twelve 12" x 20" x 4" hotel pans. One year limited parts and labor warranty. After the first year, lifetime parts warranty on the heating elements.

- CBFT** Holding & Transport Cabinet
- CBFTHS** Holding & Transport Cabinet

STANDARD FEATURES

- 12 gauge lockable transport latch.
- Tamper-proof fasteners throughout.
- Top mounted forced air heating system.
- Fully insulated.
- Fully welded removable tray slides.
- Adjustable thermostat/thermometer with security cover.
- Security cover has Lexan™ viewing port.
- Flush recessed door pull.
- Heavy duty 5" casters.
- Magnetic door closure.
- All stainless steel structural components.
- Fully welded.
- Integral dual layer fully welded corner posts.
- Super duty reinforced base.
- 270 degree door swing.
- Full perimeter bumper.
- One year limited parts and labor warranty. After the first year, lifetime parts warranty on the heating elements.
- (3) Fully welded 12 gauge hinges.
- Face mounted "sure seal gasket".

OPTIONS

- Ambient configuration
- No racking (stacked trays)


VULCAN

a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602



CBFT SERIES
HOLDING & TRANSPORT CABINET



MODEL	DIMENSIONS	CAPACITY	ELECTRICAL		NEMA	SHIPPING WEIGHTS	
	EXTERIOR		VOLTS	WATTS		LBS	KG
CBFT	28" W x 34½" D x 72" H	12 bun 24 (4" bulk)	120	1,000	115v 8' 5-15P	525	238
CBFTHS	28" W x 34½" D x 45" H	6 bun 12 (4" bulk)	120	1,000	115v 8' 5-15P	375	170



a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602

NOTE: In line with its policy to continually improve its products, Vulcan reserves the right to change materials and specifications without notice.