



VC55E SERIES

Double Deck Electric Convection Oven



Model VC55ED

Shown on optional casters



SPECIFIER STATEMENT

Double section, electric convection oven, Vulcan Model No. (VC55ED). Stainless steel front, sides, top and legs. Independently operated stainless steel doors with double pane windows. Non-sag insulation applied to the top, rear, sides, bottom and doors. Porcelain enamel on steel oven interiors measure 29"w x 22½"d x 20"h. Two interior oven lights per section. Five nickel plated oven racks per section measure 28¾" x 20½". Eleven position nickel plated rack guides with positive rack stops per section. Each section heated by electric solid sheath elements rated at 12 KW. Furnished with a two speed ½ H.P. oven blower-motor per section. Oven cool switch for rapid cool down. 208 or 240 volt, 60 Hz, 1 or 3 phase.

Exterior Dimensions:

40¼"w x 40"d (includes motor & door handles)

37¾"d (includes motor only) x 70"h on 8" legs.

NSF listed. UL listed.

Project _____

AIA # _____ SIS # _____

Item # _____ Quantity _____ C.S.I. Section 114000

MODEL

- ☐ **VC55ED** Solid state temperature dial controls adjust from 150° to 500°F with digital display enhancement. 5-hour timer with audible alarm.

STANDARD FEATURES

- Independently operated removable stainless steel doors with double pane windows
- Gentle Bake mode selector switch
- On-board diagnostics for easy servicing
- Five nickel plated grab-and-go oven racks with eleven rack positions per section
- Stainless steel front, sides, top and legs
- 25 total KW
- ½ H.P. two speed oven blower-motor
- Moisture vent
- Oven cool switch for rapid cool down
- Porcelain enamel on steel oven interiors
- One year limited parts and labor warranty

OPTIONS

- ☐ Casters
- ☐ 480V/60 Hz/1 or 3 phase
- ☐ Second year extended limited parts and labor warranty

ACCESSORIES (PACKAGED AND SOLD SEPARATELY)

- ☐ Stainless steel rear motor enclosure
- ☐ Extra oven rack(s)
- ☐ Rack hanger(s)
- ☐ Stainless steel drip pan
- ☐ Down draft flue diverter for direct vent connection

VC55E SERIES – Double Deck Electric Convection Oven

Approved by _____ Date _____ Approved by _____ Date _____



OPTIONAL VOLTAGES

□ 480 volt, 60 Hz, 3 phase

CLEARANCES

	Combustible	Non-Combustible
Rear	2"	2"
Right Side	4"	4"
Left Side	1"	1"

INSTALLATION MANUAL



CAD and/or Revit Files Available

Model	Total Conn. KW	3 Phase Load KW per Phase			Nominal Amps per Line Wire									1 Phase		Weight			
					3 Phase											With Skid & Packaging		Without Skid & Packaging	
					208 Volt			240 Volt			480 Volt								
		X-Y	Y-Z	X-Z	X	Y	Z	X	Y	Z	X	Y	Z	208V	240V	Lbs.	KG	Lbs.	KG
VC55E	25	8	8	9	70	66	70	66	58	66	28	30	30	120	104	880	400	778	352

As continued product improvement is a policy of Vulcan, specifications are subject to change without notice.